

# NH 480 S in 55 HP (2 WD)



Engine Power	55HP
Operating Weight	1710Kg.
No.of Cylinders	3
Bore Stroke	100x115mm.
Piston Displacement	2710cc
Maximum Power	@ 2500rpm 55HP
Maximum Torque	@ 1500rpm 22.7Kgm
Pump	Distribution Injection type with mechanical speed governor
Battery	12 Volts 90/95 Ah
Air Filter	Oil bath with pre cleaner and Semi automatic dust unloader
Fuel Filter	02 replaceable cartridges
Fuel Tank	54 Liters
Transmission	Gear box with constant mesh gears:8 forward and 2 reverse speeds: Synchronmesh on 3rd,4th,7th,& 8th speeds.
Brakes	Service Dry Band type with mechanical control.
Brakes (Parking)	With hand lever, on right side of operator.
Steering	Manual,Recirculating ball type, Centre relay lever Joint to lubricated for life.
Driver's seat	Fully upholstered, with parallelogram suspension ,adjustable to driver's weight.
Power Take Off	540rpm(1 318" - 6 spline Shaft)@ 2160 engine rpm.
Hyd. Pump	Gear type pump driven from engine.
Pump Capacity	22.7 L/min
Maximum lifting capacity	1450 Kg.
Tyre (Front)	6.00-16
Tyre (Rear)	12.1/11-28
D.T.O.	Speed same as engine -Anti clockwise.